[v5.5.1] Searching Knowledgebase (v5.5.1 and below)

All API URLs listed here must be prefixed by the root API URL.
Example: http://domain.com/kb/ or https://kb.domain.com/

Search Articles

GET api.php?call=articles&method=search

Arguments:

- **q** (optional) - A free text search. A UTF-8, URL-encoded search query of 1,000 characters maximum, including operators.
- **in** (optional) - Search mode. Specifies how to search. If this argument is omitted, it defaults to **article**.
  Valid values include:
  - *article* (search in article title, article body, meta keywords, meta description).
  - *article_title* (search in article title only).
  - *article_keyword* (by tags). Use a comma-delimited list of tags for **q** argument.
  - *article_id* (by article id). Use a comma-delimited list of article id for **q** argument.
  - *article_author_id* (by author id). Use a comma-delimited list of article id for **q** argument.
- **cid** (optional) - The id of a category to search. If specified, only matching articles posted to the category will be returned.
- **cp** (optional) - Specifies whether to search in child categories or not. If specified, articles posted to the category (**cid**) and in all child will be returned.
- **min_date** (optional) - Minimum updated date. Articles with an updated date greater than or equal to this value will be returned.The date can be in the form of a unix timestamp or mysql datetime.
- **max_date** (optional) - Maximum updated date. Articles with an updated date less than or equal to this value will be returned.The date can be in the form of a unix timestamp or mysql datetime.
- **pv** (optional) - Date mode. If specified date posted will be used instead of date updated for above 2 parameters, min_date and max_date
- **limit** (optional) - Number of articles to return per page. If this argument is omitted, it defaults to 10. The maximum allowed value is 100.
- **page** (optional) - The page number of results to return. If this argument is omitted, it defaults to 1.

Search Files

GET api.php?call=files&method=search

Arguments:

- **q** (optional) - A free text search. A UTF-8, URL-encoded search query of 1,000 characters maximum, including operators.
- **in** (optional) - Search mode. Specifies how to search, If this argument is omitted, it defaults to **article**.
  Valid values include:
  - fileall (search in title, filename, file text, meta keywords(tags), description).
  - *file_title* (search in file title only).
  - filename (search in file name only).
  - *file_keyword* (by tags). Use a comma-delimited list of tags for **q** argument.
  - *file_id* (by file id). Use a comma-delimited list of file id for **q** argument.
  - *file_author_id* (by author id). Use a comma-delimited list of file id for **q** argument.
- **cid** (optional) - The id of a category to search. If specified, only matching articles posted to the category will be returned.
- **cp** (optional) - Specifies whether to search in child categories or not. If specified, articles posted to the category (**cid**) and in all child will be returned.
- **min_date** (optional) - Minimum updated date. Files with an updated date greater than or equal to this value will be returned.The date can be in the form of a unix timestamp or mysql datetime.
- **max_date** (optional) - Maximum updated date. Files with an updated date less than or equal to this value will be returned.The date can be in the form of a unix timestamp or mysql datetime.
- **pv** (optional) - Date mode. If specified date posted will be used instead of date updated for above 2 parameters, min_date and max_date
- **limit** (optional) - Number of articles to return per page. If this argument is omitted, it defaults to 10. The maximum allowed value is 100.
- **page** (optional) - The page number of results to return. If this argument is omitted, it defaults to 1.

Search News

GET api.php?call=news&method=search

Arguments:

- **q** (optional) - A UTF-8, URL-encoded search query of 1,000 characters maximum, including operators. Queries may additionally be limited by complexity.
- **min_date** (optional) - Minimum posted date. News with an posted date greater than or equal to this value will be returned. The date can be in the form of a unix timestamp or mysql datetime.
- **max_date** (optional) - Maximum posted date. News with an posted date less than or equal to this value will be returned. The date can be in the form of a unix timestamp or mysql datetime.
- **limit** (optional) - Number of news entries to return per page. If this argument is omitted, it defaults to 10. The maximum allowed value is 100.

- **page** (optional) - The page number of results to return. If this argument is omitted, it defaults to 1.

Article ID: 446
Last updated: 23 Mar, 2017
Updated by: Leontev E.
Revision: 1
Developer Manual -> API -> [v5.5.1] Searching Knowledgebase (v5.5.1 and below)
https://www.kbpublisher.com/kb/entry/446/